




Rebite Estriado com Cabeça Redonda
Roundhead grooved pins
Remache acanalado de cabeça redonda

Material: SAE 1010/1020

d ₁	Dimensão nominal	1,4	1,6	2	2,5	3	4	5	6	8	10	12	16	20
	tol.		0 -0,05			0 -0,075			0 -0,1			0 -0,15		0 -0,20
d ₃		2,4	2,8	3,5	4,4	5,2	7	8,8	10,5	14	16	19	26	32
	tol.	± 0,2				± 0,25			± 0,3		± 0,4	0 -1,1	0 -1,3	
k		0,8	1	1,2	1,5	1,8	2,4	3	3,6	4,8	6,5	7,5	10	13
	tol.	± 0,1				± 0,15				± 0,2		+ 0,9 0		
r ≈		1,4	1,6	1,9	2,4	2,8	3,8	4,6	5,7	7,5	8	9,5	13	16,5
f ≈		0,5			0,7	1	1,15			2	2,5			3
tol.		+0,05 0			± 0,05						± 0,1			
ljs15	Diâmetro Sobre as Bordas do Entalhe													
3	1,50													
4	1,70													
5	2,15													
6	2,70													
8	3,20													
10	4,25													
12	5,25													
16	6,30													
20	8,30													
25	10,35													
30	12,36													
35	16,40													
40	20,50													

Exemplos de uso:



Outras medidas, sob consulta.
Other dimensions by request.
Otras medidas bajo consulta.

Ref:

Exemplo: Ref.= **Rebite Estriado-**
 Exemple: **XXxXXX**
 Ejemplo: d l

DIN 1476 3x8

Ref.= Pino Entalhado-3x8