





Cilíndrico Entalhado
Grooved pins, full length
parallel grooved with pilot.
Pasador estriado cilíndrico.

Material: SAE 1010/1020

d	mm	1,5	2	2,5	3	4	5	6	8	10	12	14	16	20	25	
tol.		h9					h11									
d ₂	tol.	+0,05 0			±0,05						±0,1					
a	+1 0	0,7	0,7	1	1	1,5	1,5	2	2	2,5	2,5	2,5	2,5	3	3	
c	≈	0,2	0,25	0,3	0,4	0,5	0,6	0,8	1	1,2	1,6	1,6	2	2,5	3	
1 js15		Diámetro sobre Entalhe - d ₂														
10																
12																
16		1,60														
20			2,15	2,65												
25					3,20											
30						4,25										
35							5,25									
40								6,30								
45									8,30							
50										10,35						
55											12,35					
60												14,35	16,40			
65														20,50	25,50	
70																
75																
80																
90																
100																
110																

Exemplos de uso:



Outras medidas, sob consulta.
 Other dimensions by request.
 Otras medidas bajo consulta.

Ref:

Exemplo: Ref.= Pino Cilindrico-
 Example: $\boxed{XX} \times \boxed{XXX}$
 Ejemplo: $\boxed{d} \times \boxed{l}$
 DIN 1470 8x40
 Ref.= Pino Cilindrico-8x40