





**Pino Entalhado Paralelo com Chanfro**  
**Grooved pins, full length parallel grooved with chamfer**  
**Pasador estriado cilíndrico**

**Material: SAE 1010/1020**

d	mm	0,8	1	1,2	1,5	2	2,5	3	4	5	6	8	10	12	14	16	20	25	
	tol.	h9								h11									
d <sub>2</sub>	tol.	+0,05 0				= 0,05						= 0,1							
c	≈	0,1	0,12	0,16	0,2	0,25	0,3	0,4	0,5	0,6	0,8	1	1,2	1,6	1,6	2	2,5	3	
f	≈	0,55	0,57	0,6	0,8	0,9	1,2	1,3	1,8	2	2,5	2,8	3,5	3,7	4	4,3	5,2	6	
1 js15		Diâmetro sobre Entalhe - d <sub>2</sub>																	
4																			
5																			
6	0,83																		
8		1,05																	
10			1,25																
12				1,60															
16					2,15														
20						2,65													
25							3,20												
30								4,25											
35									5,25										
40										6,30									
45											8,30								
50												10,35							
55													12,35						
60														14,35					
65															16,40				
70																20,50			
75																	25,50		
80																			
90																			
100																			
110																			
120																			

**Exemplos de uso:**



**Outras medidas, sob consulta.**  
 Other dimensions by request.  
 Otras medidas bajo consulta.

**Ref:**

Exemplo: Ref.= Pino Entalhado-  
 Example: XX x XXX  
 Ejemplo: d l  
 DIN 1473 8x40  
 Ref.= Pino Entalhado-8x40