





Rebite Estriado com Cabeça Chata
Countersunk head grooved pins
Remache acanalado de cabeça plana
Material: SAE 1010/1020

d_1	Dimensão nominal	1,4	1,6	2	2,5	3	4	5	6	8	10	12	16	20
	tol.		0 -0,05		0 -0,075		0 -0,1		0 -0,15		0 -0,15		0 -0,2	
d_3		2,5	2,8	3,5	4,4	5,2	7	8,8	10,5	14	16	19	26	31,5
	tol.	±0,2			±0,25			±0,3		±0,4	0	0		
k		0,7	0,8	1	1,2	1,4	2	2,5	3	3,9	4	4,6	6,5	9,5
	tol.	±0,1				±0,15				±0,2			+0,9 0	
a		75 °												60 °
f	≈	0,5		0,7	1	1,15		2		2,5		3		
tol.		+0,05 0		±0,05						±0,1				
1js15		Diâmetro Sobre as Bordas do Entalhe												
3														
4		1,50	1,70											
5				2,15	2,70									
6						3,20								
8							4,25							
10								5,25						
12									6,30					
16										8,30				
20											10,35			
25												12,35		
30													16,40	
35														20,50
40														

Exemplos de uso:


Outras medidas, sob consulta.
 Other dimensions by request.
 Otras medidas bajo consulta.

Ref:

Exemplo: Ref.= **Rebite Estriado-**
 Exemplo: **XXxXXX**
 Ejemplo: **d l**
 DIN 1477 2x6
 Ref.= **Rebite Estriado-2x6**